


ROHS
Compatible

NOTE:



- 1.MECHANICAL PERFORMANCE,
1-1.INSERTION FORCE: 0.5~2.0kgf.
1-2.REMOVAL FORCE: 0.8kgf~2.0kgf.
1-3.DURABILITY: 10000 CYCLES.
- 2.ELECTRICAL PERFORMANCE,
2-1. CURRENT RATING:3.0A
VOLTAGE RATING:5.0V
2-2. LLCR:
VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX.
SHIELD: 50mΩ/MAX.
LLCR MAX. CHANGE OF ALL PINS: 10mΩ.
2-3.INSULATION RESISTANCE: 100MΩ MIN
2-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
3. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -25°C~+85°C.
- 4.IR REFLOW:
THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 260°C.
5. WATER PROOFNESS:THIS PRODUCT IS BASED ON IPX7(1.0M 30min).

U5 172- 24P x 10.48L x
名称 流水号 PIN位 N;母座 L;长度 F;防水

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

加防水圈示意图

7	Run-RING	1PCS	Silica gel	BLACK
6	Middle clip	1PCS	STAINLESS STEEL	镀镍 30u"
5	SHELL	1PCS	STAINLESS STEEL	镀镍 30u"
4	Bracket	1PCS	STAINLESS STEEL	镀镍 50u"
3	CONTACT	1SET	Brass	半金镍 1u"
2	SHELL HOUSING	1PCS	LCP UL94-V0	BLACK
1	HOUSING	1PCS	LCP UL94-V0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	REMARKS

DESIGN	Li Jinwei	SCALL			DRAWG NO. U5172-24PN10.48LF
DRAWING	Wu Qifa	UNIT	mm		
CHECK	Zheng Jinxian	SIZE	A4: 210 * 297		
APPROVAL	Liu Xiaohong	DATE	2020-06-10		

TOLERANCE	
X.X ±0.30	X.°±2°
.XX ±0.20	.X°±1°
.XXX ±0.10	.XX°±0.5°

TITLE:
防水24P四脚插板DIP+SMT 带柱 10.35L IPX7



广东宏煜盛电子科技有限公司
Guangdong Hongyusheng Electronic Technology Co., Ltd.
TEL:0752-6632356 <https://www.hystypec.com>